

you can throw at it."

- Ryan Anderson

# **EXPERIENCE THE DERALE DIFFERENCE...**





P/N:"15876"-"Hyper-Cool"Extreme Remote"Transmission"Cooler"(x2)











[E/VM/NET TO]

NESTOR CAMACHO KING OF THE HAMMERS

Transmission Cooler



JASON SCUDELLARI
CREATOR - SO CAL QUARANTINE CRUISE

## **QUALITY, DURABLITY and SUPERIOR PERFORMANCE!**



### **ELECTRA-COOL REMOTE COOLER**

- 16 pass Tube & Fin cooler -6AN inlets
- 10" 650 CFM Electric Fan
- 15 3/4" L x 11 1/2" W x 5" D



### **BRUSHLESS A12 DUAL POWERPACK**

- 4400 CFM Raw aluminum Shroud
- PWM temp sensor Control maintains 185°F
- Plugin wire harness/hardware included
- 26" L x 18" W x 2 3/4" D

P/N: 16822

### P/N: 14208



#### FORD TRANSMISSION COOLING PAN

- Fits Ford E40D. 4R100. 5R110 & 5R110W
- Minimum 7gts. 10oz fluid capacity
- Features 5/8" cooling tubes, magnetic drain plug & 1/8" temp sender port

P/N: 35611



### LS ENGINE OIL COOLER ADAPTER

- 6061 Billet Aluminum Black Anodized
- 7/8-14 ORB (-10AN) up to 20 GPM flow
- Two additional 1/8" NPT Oil Ports
- Clears most long tube headers for LS swaps



### **HI-FLOW RACING COOLER**

- 18 Row Cooler 20 GPM (7/8-14 ORB)
- 9" 625 CFM Waterproof Electric Fan
- 11 7/8" L x 12 3/8" W x 6 5/8" D

### P/N: 14207



### **GM TRANSMISSION COOLING PAN**

- Fits Chevrolet/GMC 4L80E
- Up to 4qts. 16oz fluid capacity
- Features 5/8" cooling tubes, magnetic drain plug & 1/8" temp sender port



### PORTS L'R REMOTE FILTER MOUNT

- Black Powdercoat Finish
- Designed to fit 2 1/2" to 3 1/2" oil filters
- Can be rotated 180°F to reverse flow
- 7/8-14 ORB (-10AN) ports

### P/N: 51908



### **SERIES 10000 STACK PLATE COOLER**

- 19 Row Cooler with -8AN Alum. Fittings
- Aluminum construction tested to 250 PSI
- 13" W x 7 1/2" H x 2" D\*
  \*Cooler dimensions w/o bracktets



A17 SINGLE POWERPACK

• 17" - 2400 CFM Fan with 265-watt motor

• Designed for puller applications

• 22 1/4" W x 17 5/8" H x 3" D

### HIGH OUTPUT SINGLE RAD FAN

- 17" Dia. 2400 CFM Fan w/ 265-watt two speed motor
- Designed for pusher/puller applications
- 16 7/8" W x 16 7/8" H x 2 5/8" D



### **FAN CLUTCH FAN**

- · Rated up to 8.000 RPM
- Steel fan blades w/ black powder coated finish
- 17 1/4" Dia. x 1 15/16" D with 2 3/8" - 2 5/8" Bolt Flange



### ENGINE OIL FILTER RELOCATION KIT

- Allows oil filter to be moved to a more convenient location
- Ports Up Engine Spin-on Adapter & Filter Mount
- 3/4-16 engine thread size

P/N: 13200



### **POWER STEERING COOLER KIT**

- Designed to extend pump and seal life
- Reduces heat-related pump failure
- Universal application
- 12 3/4" W x 2 5/8" H x 3/4" D

### P/N: 16797



### PWM ELECTRIC FAN CONTROLLER

- PWM controls fan(s) speed from 0-100%
- Multiple fan controller (70 amp capacity)
- Constantly adjusts fans speed to maintain coolant temperatures from 130°F to 230°F



### **HEAVY DUTY FLEX FAN**

- Rated up to 10,000 RPM
- Stainless steel blades w/ powder coated hub
- 17 1/4" Dia. x 2 3/8" D with 1 3/4" - 2 1/4" Bolt Flange

P/N: 15708



### PORTS UP REMOTE FILTER MOUNT

- Cast aluminum
- Designed to fit 2 1/2" to 3 1/2" oil filters
- 3 bolt heavy duty flange
- 1/2" NPT inlet/outlet ports

**Check out the full line at... DERALE.COM** 





Distributed By: